



HD 715

Cold water high-pressure cleaner with 3-phase motor and special tubular frame.





1 Cage frame

- Robust, portable tubular steel frame.
- Integrated carrying handle and crane attachment point.

2 Wall mounting

- Space-saving storage.
- Machine and accessories are safely stored.

TECHNICAL DATA AND EQUIPMENT

KARCHER



HD 715

Specially designed for painters and façade cleaners

- Rotatable stainless steel spray lance
- Continous pressure regulation

Technical data		
Order No.		1.151-500.0
EAN code		4039784727656
Supply voltage	Ph / V / Hz	3 / 400 / 50
Flow rate	l/h	250-700
Working pressure	bar / MPa	10-150 / 1-15
Max. pressure	bar / MPa	175 / 17.5
Max. inlet temperature	°C	60
Connection load	kW	4.7
Weight	kg	29
Dimensions (L × W × H)	mm	500 × 310 × 350
Equipment		
Spray gun		Easy Press trigger gun
Spray gun with soft grip		1
Pressure hose	m	15
Spray lance	mm	850
Triple nozzle (0°/25°/40°)		touchless
Anti-twist system		1
Pressure cut-off		1
Servo Control		-
Included in delivery.		

KARCHER





14









12-13

	3, 5
	15

18 6.391-351.0

DN 8

▲ Extension hose.

400 bar

10 m

Longlife 400 high-pressure hose,

■ Included in delivery. □ Available accessories.

10 m, DN 8,





		Order No.	ID	Max. working pressure	Length		Price	Description	
Standard with unions on both sides	5							·	
High-pressure hose, 10 m, ID 8, _315 bar, extension piece	1	6.391-342.0	DN 8	315 bar	10 m				
High-pressure hose, 15 m, ID 8, 315 bar, including rotary coupling	2	6.390-010.0	DN 8	315 bar	15 m				
High-pressure hose, 20 m, ID 8, 315 bar, extension piece	3	6.390-031.0	DN 8	315 bar	20 m				
High-pressure hose, 30 m, ID 8, including rotary coupling	4	6.390-293.0	DN 8	315 bar	30 m				
High-pressure hose, 15 m, ID 10,	5	6.390-023.0	DN 10	220 bar	15 m				
220 bar, extension piece Longlife 400 with unions on both s	ides		1						_
High-pressure hose Longlife 400, 10 m, ID 8, including rotary cou- pling		6.388-083.0	DN 8	400 bar	10 m			10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 x 1.5, with kink protection.	
Longlife 400 high-pressure hose, 10 m, DN 8, extension piece	7	6.391-354.0	DN 8	400 bar	10 m				
High-pressure hose Longlife 400, 15 m, ID 8, including rotary cou- pling	8	6.389-709.0	DN 8	400 bar	15 m			With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose Longlife 400, 20 m, ID 8, extension	9	6.390-027.0	DN 8	400 bar	20 m			with rotary coupling, 2 x M 22 x 1.5	
High-pressure hose Longlife 400, 30 m, ID 8, including rotary cou- pling	10	6.390-294.0	DN 8	400 bar	30 m			With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose 1.5 m, ID 8, including connectors	11	6.390-178.0	DN 8	400 bar	1.5 m			1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink pro- tection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	
Food industry version with unions	on bot	h sides			·				
High-pressure hose, 10 m, DN 8, suitable for the food industry, extension piece	12	6.389-479.0	DN 8	250 bar	10 m			10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.	
High-pressure hose, 20 m, ID 8, suitable for food industry, exten- sion piece	13	6.389-581.0	DN 8	250 bar	20 m			20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	
Longlife food design with screw co	nnectio	ons at both ends					-		
High pressure hose food ID 8, 10 m	14	6.391-864.0	DN 8	400 bar	10 m			Longlife HP hose for use in the food industry. Außen- decke## animal-grease-resistant, non-colour-bleeding mate	
High-pressure hose food industry 400 bar, 20 m, ID 8, including rotary coupling	15	6.391-887.0	DN 8	400 bar	20 m			rial. With rotary coupling, 2 x M 22 x 1,5	
Standard High-pressure hose, 15 m, ID 6, AVS gun connection	16	6.391-394.0	DN 6	250 bar	15 m				
Longlife 400		I	1	1		1		1	-
Longlife 400 high-pressure hose, 10 m, DN 6, M 22 x 1.5	17	6.391-882.0	DN 6	400 bar	10 m			With patented AVS connection in the trigger gun (piv- ot-mounted).	



				Max. working			
Longlife food design		Order No.	ID	pressure	Length	Price	Description
High-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun con- nection	19	6.391-888.0	DN 6	400 bar	15 m		Longlife HP hose for use in the food industry. Außen- decke## animal-grease-resistant, non-colour-bleeding mate- rial. With patented AVS connection in the pistol (pivot mounted)
Special hoses							
High-pressure hose 1.5 m, ID 8, including connectors, outlet bend	20	6.388-886.0	DN 8	400 bar	1.5 m		

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill\blacksquare$ Extension hose.



		Order No.	Flow rate		Price	Description	
Easy Press high-pressure trigger g	un with	holding force r	eduction (Kärcher p	atent)			
Easy Press HP trigger gun with soft grip	1	4.775-463.0				Easy press high-pressure trigger gun with softgrip. For high-pressure hoses DN 6 and DN 8 with 11 mm swivel diameter.	
Trigger guns							
High-end HP trigger gun	2	4.775-823.0					
Quick connect							
Quick coupling	3	6.401-458.0				For quick change of different spray lances and accessories. Optimum adaption to Kärcher accessories, especially for connection between trigger gun and spray lance. With M22 x 1,5 female.	
Male coupling	4	6.401-459.0				Hardened stainless steel nipple for quick coupling 6.401- 458. With M22 x 1,5 male.	

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill\blacksquare$ Extension hose.

KARCHER



			Max. working					
		Order No.	pressure	Length			Price	Description
Rotating spray lances		1						
850 mm spray pipe, rotatable	1	4.760-663.0	300 bar	840 mm				850 mm stainless steel lance (manual coupling) with ergo-
								nomic handle for ease of use and protection. Rotatable 360° I under pressure.
600 mm spray pipe, rotatable	2	4.760-664.0	300 bar	600 mm				600 mm stainless steel lance (manual coupling) with ergo-
								nomic handle for ease of use and protection. Rotatable 360° [under pressure.
1050 mm spray pipe, rotatable	3	4.760-660.0	300 bar	1050 mm				1050 mm stainless steel lance (manual coupling) with ergo-
								nomic handle for ease of use and protection. Rotatable 360° [under pressure.
1550 mm spray pipe, rotatable	4	4.760-661.0	300 bar	1550 mm				1550 mm stainless steel lance (manual coupling) with ergo-
								nomic handle for ease of use and protection. Rotatable 360°
2050 mm spray pipe, rotatable	5	4.760-662.0	300 bar	2050 mm				under pressure. 2050 mm stainless steel lance (manual coupling) with ergo-
2000 mini spray pipe, rotatable		4.700 002.0	500 bui	2030 1111				nomic handle for ease of use and protection. Rotatable 360° [
								under pressure.
Spray lances			0501	050	1	1	1	
Vibrasoft lance	6	6.415-951.0	250 bar	950 mm				The spring-loaded 360° loop handle significantly reduces the vibrations on the spray lance, reducing the physical burden
								on the user, e.g. when working with the dirt blaster.
Spray lance								
250 mm lance, non-rotatable	7	4.760-667.0		250 mm				250 mm stainless steel lance. With manual coupling. Non-ro- tatable.
Double lance			1	L	1	1		
Double lance 960 mm	8	6.394-665.0	310 bar	960 mm				960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (
								e.g. stable cleaning).
Variable pressure spray lance								
Variable pressure spray lance	9	4.760-362.0		670 mm				670 mm variable pressure lance with integrated pressure
								gauge. Variable pressure adjustment on the handle. Nozzle
Variable pressure lance	10	4.760-230.0		1040 mm				connector: M 24 x 1.5. Low pressure detergent application. 1040 mm pressure adjustable lance with integrated pres-
	10							sure gauge. Variable pressure adjustment on the handle.
								Nozzie connector: M 24 x 1.5. Low pressure detergent appli-
Adapter for variable pressure spr	av lance						I	cation.
Adapter for variable pressure		4.762-075.0	1		1	1		For items 4.760-230 and 4.760-362 for mounting accesso-
lance	11	4.702 075.0						ries to lance, M 24/18 x 1.5
Angular spray lance								
Spray lance for toilets and rain	12	4.760-073.0						Stainless steel lance WC and gutter with nozzle insert. Spe-
gutters								cially shaped for effective and hygienic cleaning of gutters and toilets.
Flexible spray lance								and tonets.
Flexible lance 1050 mm	13	6.394-654.0	210 bar	1050 mm				1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.
Telescopic spray lance								
Telescopic spray lance	14	6.394-690.0	225 bar]
Strap for telescopic spray pipe	15	6.373-987.0						Convenient strap for relief when working with the telescop-
								ic spray lance (6.394-690). The burden is optimally distrib-
■ Included in delivery. □ A	Vailab	e accessories.	▲ Extension h	1	1	1		uted on the body and longer periods of use are possible.



		Order No.	Max. working pressure	Length		Price	Description	
Gutter cleaning lance	16	2.642-305.0					The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance Underbody lance	17	4.760-245.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	



		Order No.				Price	Description
Miscellaneous							
Backflow check valve	1	6.412-578.0					To prevent cleaning agent from entering the drinking water system at low supply pressure.
Included in delivery.] Available	e accessories.	▲ Extension h	ose.			

□ Available accessories. ▲ Extension ho cluded in delivery.

KÄRCHER

				5		6		
9 10								
		Order No.	Flow rate	Nozzle size	Diame- ter		Price	Description
Hard surface cleaner FRV 30					1 1			
FRV 30 surface cleaner	1	2.642-999.0						
Rubber lip for FRV 30	2	2.642-910.0						For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.
Extension hose 5 m	3	4.440-939.0						5m extension hose for FRV 30. Connection sleeve included.
ABS hose fastening	4	2.642-528.0						
ABS dirt trap	5	2.642-532.0						
Hard surface cleaner FR 30								
FR 30	6	2.642-997.0			300 mm			
FR 30 Me surface cleaner								
Hard surface cleaner FR 30 Me	7	2.640-355.0			300 mm			Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.
Machine-specific nozzle kits for FF	2							
Nozzle kit for surface cleaners	8	2.640-401.0	500-650 l/h					Nozzle kit includes power nozzles and unions. For Kärcher urface cleaners (500 to 650 l/h).
Machine-specific nozzle kits for FF								
Nozzle kit 045 - for FRV 30	9	2.642-432.0		45				
FRV 30 Me surface cleaner								
FRV 30 Me	10	2.642-911.0						
FRV 30 Me extension hose	11	4.441-040.0						
■ Included in delivery. □ Av	/ailabl	e accessories.	Extension h	0SP				

KÄRCHER





ER

10













		Order No.			Pri	ice	Description	
Nozzle union								
Nozzle connector	1	5.401-210.0					For protecting and connecting Kärcher power nozzles to spray lances (M 18 x 1.5 IG).	
Spacer (including nozzle union)								
Spacer (includes nozzle screws)	2	5.394-294.0					Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces. Mounts directly to lance.	
Coupling parts								
Articulated joint	3	6.987-705.0					This articulated joint with variable angle adjustment (up to an angle of 120°) is recommended for cleaning hard to reach areas. Fits directly on the spray lance.	ב
Rotary coupling								
Rotary coupling	4	4.401-091.0					Kårcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 [m. With grip protection.	ב
Coupling								
Coupler -2xM22x1,5	5	4.403-002.0					Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x [M 22 x 1.5 m.	ב
Connector								
Nozzle screws / screw socket	6	4.402-022.0					Nozzle connector/screw connector for connecting high-pres- sure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.]
Adapters			I	I			1X W 10 X 1.5.	
Adapter M 22 - Swivel	7	4.424-004.0					M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	2
Cleaning agent injector								
Cleaning agent injector for high pressure (without nozzle)	8	3.637-170.0					Cleaning agent dosage at high pressure 3 - 5 %	
Cleaning agent injector for high and low pressure (without nozzles)	-	3.637-001.0					Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Machine-specific nozzle kit with or	der no	. 3.637-170.0						
Nozzle kit HD 500-700 l/h	10	4.769-045.0					For HD 500 - 700 I/h. Consists of nozzle insert + HP power nozzle + union	
Nozzle insert with order no. 3.637-								
Nozzle insert up to 1,100 l/h - high pressure	11	4.769-003.0					Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Nozzle insert up to 1,100 l/h - low pressure ■ Included in delivery. □ Av	12	4.769-001.0					For low pressure with machines up to 1.100 l/h	



		Order No.	Nozzle size		Price	Description	
		order No.	NOZZIE SIZE		Price	Description	_
HP nozzle spray angle 0°							
High-pressure nozzle spray angle °O	1	2.884-534.0	45			High-pressure nozzle with powerful jet for extremely stub- born dirt.	
Power nozzle spray angle 15°							
Power nozzle spray angle 15°	2	2.883-389.0	45			Fan jet nozzle with 15° spray angle suitable for stubborn dirt.	
Power nozzle spray angle 25°						· · · · · · · · · · · · · · · · · · ·	
Power nozzle spray angle 25°	3	2.883-398.0	45			Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.	
25° power nozzle for cleaning agent suction	4	2.884-521.0	250				
Power nozzle spray angle 40°						· · · · · · · · · · · · · · · · · · ·	
Power nozzle spray angle 40°	5	2.884-523.0	45			Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	

KÄRCHER



		Order No.	Max. working pressure	Nozzle size		Price	Description	
Triple nozzles							1	
Triple jet nozzle 045	1	4.767-153.0	300 bar	45				
Triple nozzle, touchless changeover								
Triple nozzle, touchless changeo- ver	2	4.767-002.0		45			Triple nozzle with high-pressure pencil jet (25°) and low-pressure fan jet (40°). Fast and easy jet changeover by turning the nozzle.	
Angled vario nozzle 0-90°								
Spezial nozzle 0005	3	4.763-039.0		50			Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces.	
Dirt Blaster, small								
Dirt blaster	4	4.767-100.0	180 bar	45			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 180 bar, 18 MPa, 60°C.	
Dirt blaster - more Performance	5	4.767-232.0	180 bar	45			Up to 50% higher cleaning and area performance than its predecessor: with the new performance dirt blaster (nozzle size 045), power losses have been minimised and the spray quality maximised.	
Dirt blaster, large								
Dirt blaster	6	4.763-988.0	300 bar	45			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	
Inaktiv							`	
Dirt blaster - with changeover to low pressure cleaning agent intake	7	4.763-951.0	300 bar	50				
Inaktiv							•	
Dirt blaster with changeover to fan jet	8	4.763-957.0	300 bar	50				



		Order No.	Nozzle size		Price	Description	
Wet blasting attachment (without n	ozzle)					
Wet blasting attachment with flow control (without nozzles)	1	4.762-010.0				Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abra- sive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	2	4.762-022.0				Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abra- sive to the high-pressure jet. Without flow control.	
Nozzle kits for wet jet unit							
Nozzle kit for wet jet unit 045	3	2.637-901.0	45			Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kårcher wet blasting attachment per- formance. Only in combination with wet blasting attachment 4.762-010/-022.	
Boron carbide nozzle							
Boron carbide nozzle, for ma- chines up to 1,000 l/h	4	6.415-084.0	6 mm			In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	



		Order No.	Max. working pressure	Nozzle size	Diame- ter	Price	Description	
Pipe cleaning hose, ID 6								
Pipe cleaning hose, DN 6, 20 m, max. 120 bar	1	6.390-028.0	120 bar				The 20 m pipe cleaning hose is a highly flexible high pres- sure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, DN 6, 30 m, max. 120 bar	2	6.390-029.0	120 bar				30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	
Pipe cleaning hose, DN 6, 20 m, max. 250 bar	3	6.390-030.0	250 bar				The 20 m pipe cleaning hose is a highly flexible high pres- sure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning nozzle				·	<i>.</i>			
Pipe cleaning dirt blaster D 25 / _060	4	6.415-945.0		60	25 mm		The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the	
Pipe cleaning dirt blaster D 30 / 060	5	6.415-947.0		60	30 mm		necessary forward movement, as well as convenient han- dling.	
Pipe cleaning dirt blaster D 35 / 060	6	6.415-949.0		60	35 mm			
Rotating pipe cleaning nozzle	7	6.415-428.0		50	16 mm		Pipe cleaning nozzle with four rotating jets and inner thread. Different spray directions. The hose moves freely through the pipe. With R 1/8" connection.	



		Order No.	Flow rate		Price	Description
Cup foam lance						
Cup foam lance	1	6.394-668.0	1200 l/h			Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its com- pact design.
1-litre cleaning agent container for foam lance	2	6.414-954.0				
Inno Foam Kit						
Inno Foam Set with detergent injector	3	2.640-151.0				High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set						
Easy Foam Set with RM injector	4	2.640-691.0				HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Nozzle kits for Inno/Easy Foam Set						
Nozzle kit 060 for Inno / Easy Set 600-700 l/h	5	2.640-687.0	600-700 l/h			Optimal adaptation to different machine outputs for eco- nomic use.
Foam nozzle mounting kit						
Foam nozzle attachment kit	6	2.637-926.0				Foaming agent kit. The foam nozzle is ideal for use in sani- tary areas and the food industry and wherever long applica- tion times are necessary.

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill \blacktriangle$ Extension hose.

KARCHER



		Order No.	Length		Price	Description
Automatic, self-winding hose reels						
Automatic hose reel, powder-coat- ed steel / plastic	1	6.392-975.0	20 m			Automatic hose reel for 20 m high-pressure hose. The con- sole is made from powder-coated steel, the drum is made from plastic.
Automatic stainless steel / syn- thetic material hose drum	2	6.392-965.0	20 m			Automatic hose reel for 20 m high-pressure hose. The con- sole consists of stainless steel, the drum is made from plas- tic.
Automatic hose reel, coated	3	2.639-919.0	20 m			Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.
Powder-coated swivel holder	4	2.639-931.0				Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. [Rotatable 120°. Galvanised steel.
Automatic hose reel, stainless steel, includes swivel holder	5	6.391-421.0	20 m			Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.
ABS automatic stainless steel hose drum	6	2.641-866.0	20 m			High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.
ABS pivoting stainless steel wall bracket	7	2.641-867.0				Swivelling wall bracket made of high-grade steel (for 2.641- 866). This makes maximum flexibility and convenience possible when working with the HP hose.

KÄRCHER





		Order No.	Length	Diameter		Price	Description
Starting current limiter							
Starting current limiter	1	2.637-495.0					Reduces starting current in single-phase supply and protects line fuse.
Geka coupling							
Geka connector with hose barb, R 1/2"	2	6.388-461.0					with hose liner
Geka connector with hose barb, R 3/4"	3	6.388-455.0					
Geka connector with inner thread, R 3/4"	4	6.388-473.0					with female thread
Suction filter							
Water suction filter	5	6.414-956.0					
Suction filter with check valve	6	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.
Water fine filter							
Water fine filter, with adapter	7	4.730-102.0					Fine-mesh water filter, 125μ m, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles con- tained in the water. Water flow rate up to 1200 l/h. Connec- tion 3/4", with adapter, 1".
Water supply hose							
Water supply hose	8	4.440-038.0	7.5 m				NW 13 R1" / R 3/4", up to 30 °C
	9	4.440-207.0	7.5 m				NW 19 R1" / R 3/4", up to 85 °C, for pick-up
Backflow check valve							
Backflow preventer	10	2.641-374.0					To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection



		Order No.	Flow rate		Price	Description
Push-on washing brush						
Push-on washing brush	1	4.762-016.0				Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.
Rotating washing brush						
Rotating wash brush for < 800 l/h machines, natural hair bristles	2	4.762-560.0	500-800 l/h			Ε
Rotating wash brush for < 800 l/h machines, nylon bristles	3	4.762-561.0	500-800 l/h			The rotating wash brush gently removes fine dust and grime from all surfaces. Heat-resistant up to 60°C. (M 18 x 1.5, replaceable brush insert).